

TOOL FEATURES

1. Depth of clinch and penetration adjustable fully adjustable according to your sealing needs.
2. Safety prioritized equipped with a safety foot pedal.
 - Noise minimized low noise engine.
 - Production grade ideal for high volume production.
 - High speed operation 50~100 carton bottoms per hour.
 - Full mechanical no air source required.

TOOL SPECS

Weight	26 kgs (57.3 lbs)
Height	1245mm (49")
Width	600mm (23.6")
Length	910mm (35.8")
Applications	Stapling Corners on Corrugated Trays, Carton Box Sealing, Packaging



FASTENER SPECS

Model Number	Staple Type	Loading Capacity	A	B	C
MT-PB35-22	34.7mm (1-3/8") Crown Carton Staples	200	15, 18, 22mm (5/8", 3/4", 7/8")	34.7mm (1-3/8")	0.9 x 2.3mm (0.035" x 0.090")
MT-PB32-22	32mm (1-1/4") Crown Carton Staples	200	15, 18, 22mm (5/8", 3/4", 7/8")	32mm (1-1/4")	0.9 x 1.9mm (0.035" x 0.075")
MT-SB35-22	34.7mm (1-3/8") Crown Carton Staples	200	15, 18, 22mm (5/8", 3/4", 7/8")	34.7mm (1-3/8")	0.9 x 2.3mm (0.035" x 0.090")
MT-SB32-22	32mm (1-1/4") Crown Carton Staples	200	15, 18, 22mm (5/8", 3/4", 7/8")	32mm (1-1/4")	0.9 x 1.9mm (0.035" x 0.075")

