

## TOOL FEATURES

1. Robust gravity-casted engine pneumatic piston return design.
2. Hardened clinch teeth for clinch consistency & tool longevity.
3. Ergonomic rubber handle grip.
  - All metal construction.
  - Pneumatic piston return minimizes cycle time.
  - 3 nose lengths available.
  - Adjustable for left or right handed operation.

**HR7**   **HR7E**   **HR77XE**  
25mm (1")   40mm (1.6")   70mm (2.8")



## FASTENER SPECS

Type	15 GA. Bostitch RING15 / Meihotech GDH
Loading Capacity	100 Rings
Ring Height	12mm (1/2")
Crown Width	23.9mm (15/16")
Wire Dia.	1.8mm (0.07")
Open Ring Size	19mm (3/4")
Closure Ring Size	7.9~10.7mm (5/16"~27/64")

## TOOL SPECS

Weight	HR7 : 1.39 kgs (3.0 lbs) HR7E : 1.53 kgs (3.4 lbs) HR77XE : 1.72 kgs (3.8 lbs)
Height	189mm (7.4")
Width	89mm (3.5")
Length	HR7 : 335mm (13.2") HR7E : 354mm (13.9") HR77XE : 381mm (15")
Operating Pressure	5.9~7.9 bar (85~115 psi)
Applications	Bag Closure, Bedding, Automotive Seating, Wire Cages, Fencing

