




## **TOOL FEATURES**

- 1. Rotatable exhaust on enduring engine.
- 2. Sequential trigger lock ensures workplace safety.
- 3. Nail tip guide, places fastener point directly into connector holes for a fast and precise application.
- 4. Metal belt hook provides workplace convenience.
- Cushioned grip ergonomic frame provides comfort during operation.
- 6. Aluminum magazine offers balance for maneuverability.
- · Low nail lockout prevents dry fires.
- · Anti nail back up pawl boosts operation stability.
- · Compact design fits between 12" O.C. joists.





| FASTENER SPECS   |                             |
|------------------|-----------------------------|
| Туре             | 34° Paper Collated Nails    |
| Loading Capacity | 33                          |
| A                | 38~40mm (1-9/16")           |
| В                | 7.01~7.36mm (0.276"~0.290") |
| С                | 3.3mm~3.8mm (0.131"~0.148") |



| TOOL SPECS         |  |
|--------------------|--|
| Weight             | 2.0 kgs (4.4 lbs)  |
| Height             | 275mm (10.8")  |
| Width              | 92mm (3.6")  |
| Length             | 298mm (11.7")  |
| Operating Pressure | 5~8 bar (70~120 psi)   |
| Driving Power      | 59+ In-lbs @100 psi  |
| Applications       | Strapping, Joist Hangers, Hurricane Ties,<br>Rafter Ties, Post Bases, Caps Anchors |

