

INDUSTRY-LEADING C-RINGER SOLUTION

- ALL METAL CONSTRUCTION
- 3 NOSE LENGTHS AVAILABLE
- PNEUMATIC PISTON RETURN MINIMIZES CYCLE TIME
- ADJUSTABLE FOR LEFT OR RIGHT HANDED OPERATION

ROBUST GRAVITY-CASTED ENGINE
PNEUMATIC PISTON RETURN DESIGN

HARDENED CLINCH TEETH
for Clinch Consistency &
Tool Longevity

ERGONOMIC RUBBER HANDLE GRIP



Model #	Nose Length
HR7:	1" (25mm)
HR7E:	1.6" (40mm)
HR77XE:	2.8" (70mm)

FASTENER SPECIFICATION

Type:	15 GA. Bostitch RING15 Meihotech GDH
Wire Diameter:	0.07" (1.8mm)
Crown Width:	15/16" (23.9mm)
Ring Height:	1/2" (12mm)
Open Ring Size:	3/4" (19mm)
Closure Ring Size:	5/16~27/64" (7.9~10.7mm)
Tip Finish:	Sharp or Blunt
Load Capacity:	100 Rings

TOOL SPECIFICATION

Weight:	3.0 lbs (1.39kg)
Height:	7.4" (189mm)
Width:	3.5" (89mm)
Length:	HR7: 13.2" (335mm) HR7E: 13.9" (354mm) HR77XE: 15" (381mm)
Operating Pressure:	85 to 115 PSI (5.9~7.9 bars)
Firing Mode:	Trigger Fire
Applications:	Bag Closure, Bedding Automotive Seating Wire Cages, Fencing

