

### INDUSTRY-LEADING C-RINGER SOLUTION

- ALL METAL CONSTRUCTION
- PNEUMATIC PISTON RETURN MINIMIZES CYCLE TIME
- 2 CLOSURE RING SIZES AVAILABLE
- ADJUSTABLE FOR LEFT OR RIGHT HANDED OPERATION

**ROBUST GRAVITY-CASTED ENGINE**  
**PNEUMATIC PISTON RETURN DESIGN**

**HARDENED CLINCH TEETH**  
for Clinch Consistency &  
Tool Longevity

**ERGONOMIC RUBBER HANDLE GRIP**



| Model #       | Nose Length |
|---------------|-------------|
| <b>HR760:</b> | 1" (25mm)   |
| <b>HR761:</b> | 1" (25mm)   |

| FASTENER SPECIFICATION |   |
|------------------------|---|
| Type:                  | 16 GA. Meihotech 47ALD<br>Bostitch RING516G100                              |
| Wire Diameter:         | 0.063" (1.6mm)  |
| Crown Width:           | 21/32" (16.8mm)   |
| Ring Height:           | 3/8" (9mm)  |
| Open Ring Size:        | 1/2" (12.5mm)   |
| Closure Ring Size:     | <b>HR760:</b> 1/8~7/32" (3.2~5.6mm)<br><b>HR761:</b> 3/16~7/32" (4.8~5.6mm) |
| Tip Finish:            | Sharp or Blunt  |
| Load Capacity:         | 110 Rings   |

| TOOL SPECIFICATION  |   |
|---------------------|---|
| Weight:             | 2.9lbs. (1.29kg)  |
| Height:             | 7.4" (189mm)  |
| Width:              | 3.5" (89mm)   |
| Length:             | 13.2" (335mm)   |
| Operating Pressure: | 85 to 115 PSI (5.9~7.9 bars)                                      |
| Firing Mode:        | Trigger Fire  |
| Applications:       | Bag Closure, Bedding<br>Automotive Seating<br>Wire Cages, Fencing |

