

### INDUSTRY-LEADING C-RINGER SOLUTION

- ALL METAL CONSTRUCTION
- PNEUMATIC PISTON RETURN MINIMIZES CYCLE TIME
- 2 CLOSURE RING SIZES AVAILABLE
- ADJUSTABLE FOR LEFT OR RIGHT HANDED OPERATION

**ROBUST GRAVITY-CASTED ENGINE**  
**PNEUMATIC PISTON RETURN DESIGN**

**HARDENED CLINCH TEETH**  
for Clinch Consistency &  
Tool Longevity

**ERGONOMIC RUBBER HANDLE GRIP**



Model #	Nose Length
<b>HR760:</b>	1" (25mm)
<b>HR761:</b>	1" (25mm)

FASTENER SPECIFICATION	
Type:	16 GA. Meihotech 47ALD Bostitch RING516G100
Wire Diameter:	0.063" (1.6mm)
Crown Width:	21/32" (16.8mm)
Ring Height:	3/8" (9mm)
Open Ring Size:	1/2" (12.5mm)
Closure Ring Size:	<b>HR760:</b> 1/8~7/32" (3.2~5.6mm) <b>HR761:</b> 3/16~7/32" (4.8~5.6mm)
Tip Finish:	Sharp or Blunt
Load Capacity:	110 Rings

TOOL SPECIFICATION	
Weight:	2.9lbs. (1.29kg)
Height:	7.4" (189mm)
Width:	3.5" (89mm)
Length:	13.2" (335mm)
Operating Pressure:	85 to 115 PSI (5.9~7.9 bars)
Firing Mode:	Trigger Fire
Applications:	Bag Closure, Bedding Automotive Seating Wire Cages, Fencing

