

TOUGHER. FASTER. SMARTER.

- **CLUTCH MECHANISM**
- **OPTIONAL PLANETARY GEAR SYSTEM WITH NEEDLE BEARING**
- **AUXILIARY SIDE HANDLE BOOSTS CONTROL AND STABILITY FOR LEFT- AND RIGHT-HANDED USERS**

ENGINEERED COMPOSITE HOUSING

Provides Comfort and Durability



VARIABLE SPEED TRIGGER

Keeps Up with Your Pace of Work

ONE-HANDED REVERSE SWITCH

Minimizes Downtime

REAR EXHAUST

Provides Workplace Comfort

DRIVE SPECIFICATION

Free Speed:	12,000 rpm
Max Torque:	900 in-lbs (102 Nm)
Working Torque:	300~480 in-lbs (34~54 Nm)
Energy:	0.5 HP
Air Inlet:	1/4" PT-19 or NPT-18
Avg. Air Consumption:	4 CFM (113 L/min)

TOOL SPECIFICATION

Weight:	2.2lbs. (1.0kg)
Height:	6.1" (156mm)
Width:	1.7" (43mm)
Length:	7.1" (181mm)
Operating Pressure:	90 psi (6.2 Bar)
Actuation Mode:	Trigger Actuated
Applications:	wood screws, wall boards assembly line work.

