

**340MM
(13.4")**

COMPACT HEIGHT

fits between
standard C-C studs



TOOL FEATURES

- 1 METAL EXHAUST COVER
 - 2 CUSHIONED RUBBER GRIP AND ERGONOMIC FRAME
 - 3 46MM WIDE RAFTER HOOK
 - 4 TRIGGER LOCK ENSURES WORKPLACE SAFETY
 - 5 TOOL-FREE DEPTH ADJUST
 - 6 DURABLE NOSE, SERRATED CONTACT ARM, NOSE SHROUD AND NO-MAR TIP
 - 7 ROBUST NYLON MAGAZINE WITH INDUSTRY LEADING DURABILITY
- FCN90B-ST AVAILABLE AS AN OPTIONAL "SEQUENTIAL FIRE ONLY" TOOL
 - ROBUST DESIGN WITH PROVEN DURABILITY
 - FAST CYCLE TIME BOOSTS EFFICIENCY

TOOL SPECIFICATIONS

Weight	7.7lbs. (3.5kg)
H x W x L	13.2" x 5.2" x 11.9" 335mm x 131mm x 302mm
Operating Pressure	70 to 120 PSI (5-8 bars)
Driving Power	1000 in.-lbs.
Firing Mode	Contact Fire

FASTENER SPECIFICATIONS

Collation	15° Wire Collated
Fastener Length	2"~3-1/2" (50~90mm)
Head Diameter	0.256"~0.303" (6.5~7.7mm)
Shank Diameter	.099"~.148" (2.5~3.8mm)
Shank Type	Smooth, Screw, Ring
Load Capacity	225~300

APPLICATIONS: Framing, Sheathing, Decking, Subfloors, General Construction

