

MOST PROVEN FRAME NAILING SOLUTION

- CYLINDER VALVE DRIVING SYSTEM
- QUICK RESPONSE AND RAPID, POWERFUL DRIVING
- OPTIONAL TOOL-FREE DEPTH ADJUST
- AVAILABLE WITH CONTACT FIRE OR SEQUENTIAL TRIGGER

ONE-PIECE ALUMINUM CAP

MOVING CYLINDER

Generates Minimum Recoil

ERGONOMIC FRAME

Provides Mobility and Balance

DURABLE HARDENED CLAW TIP

FLEXIBLE ALUMINUM MAGAZINE

Minimizes Deformation from Drop Impact



FASTENER SPECIFICATION

Type:	22° Plastic Collated Nails
Length:	2"~3-1/2" (50~90mm)
Shank Dia.:	0.113"~0.148" (2.9~3.8mm)
Max Head Dia. :	0.268"~0.315" (6.8~8.0mm)
Load Capacity:	70

TOOL SPECIFICATION

Weight:	8.2lbs. (3.7kg)
Height:	13.4" (340mm)
Width:	4.7" (120mm)
Length:	20.6" (523mm)
Operating Pressure:	70 to 120 PSI (5-8 bars)
Firing Mode:	Contact fire or Sequential
Driving Power	823 In-lbs.
Applications:	Sheathing, Framing General Construction

