



TOOL FEATURES

- 1 **ROTATABLE EXHAUST ON ENDURING ENGINE**
- 2 **SEQUENTIAL TRIGGER AND TRIGGER LOCK ENSURES WORKPLACE SAFETY**
- 3 **NAIL POINT VISIBILITY FOR EASE OF PLACEMENT INTO METAL CONNECTOR HOLES**
- 4 **METAL BELT HOOK PROVIDES WORKPLACE CONVENIENCE**
- 5 **CUSHIONED GRIP AND ERGONOMIC FRAME PROVIDES COMFORT DURING OPERATION**
- 6 **ALUMINUM MAGAZINE WITH IN-LINE DESIGN OFFERS BALANCE FOR MANEUVERABILITY**
- **ANTI NAIL BACK UP PAWL BOOSTS OPERATION STABILITY**
- **COMPACT DESIGN FITS BETWEEN 12" O.C. JOISTS**
- **LOW NAIL LOCKOUT PREVENTS DRY FIRES**

TOOL SPECIFICATIONS

Weight	4.4lbs. (2.0kg)
H x W x L	10.3" x 3.9" x 11.6" 263mm x 101mm x 295mm
Operating Pressure	70 to 100 PSI (5-6.9 bars)
Firing Mode	Sequential Fire

FASTENER SPECIFICATIONS

Collation	34° Paper / Plastic Collated
Fastener Length	38~40 mm (1-1/2")
Shank Diameter	Φ3.3~3.8mm (.131~.148")
Shank Type	Smooth, Screw, Ring
Load Capacity	33

APPLICATIONS: Strapping, Joist Hangers Hurricane Ties, Rafter Ties Post Bases, Caps Anchors

