

## WORK FASTER WITH MORE PRECISION

- 530 IN-LBS. OF DRIVING FORCE
- PATENTED PRECISION NAILING TECHNOLOGY
- SCN66B-CT AVAILABLE AS AN OPTIONAL "BUMP FIRE ONLY" TOOL

### ADJUSTABLE EXHAUST

Ensures Workplace Comfort

**SEQUENTIAL TRIGGER** Prevents Damage on Siding Material from Double Firing

Ensures Workplace Safety

### TOOL-FREE DEPTH ADJUST

### ONE-STEP OPENING MAGAZINE LATCH

### NO-MAR PAD INCLUDED



### CUSHIONED RUBBER GRIP ERGONOMIC FRAME

Provides Comfort and Balance

**METAL BELT HOOK**  
for Workplace Convenience

**ROBUST NYLON MAGAZINE**  
Industry Leading Durability

### PRECISION NAILING TECHNOLOGY

Minimizes Driver Mark Occurrences and Maximizes Line of Sight in Operation

### PRECISION NAILING TECHNOLOGY



### FASTENER SPECIFICATION

<b>Collation:</b>	0° Plastic Collated
<b>Fastener Lengths:</b>	32~65mm (1-1/4"~2-1/2")
<b>Shank Dia.:</b>	Φ2.0~2.8mm (.080"~.110")
<b>Shank Type:</b>	Smooth, Screw, Ring
<b>Load Capacity:</b>	300

### TOOL SPECIFICATION

<b>Weight:</b>	5.2lbs. (2.3kg)
<b>Height:</b>	11.4" (290mm)
<b>Width:</b>	5.7" (146mm)
<b>Length:</b>	11.4" (290mm)
<b>Operating pressure:</b>	70 to 120 PSI (5-8 bars)
<b>Firing mode:</b>	Sequential Trigger
<b>Applications:</b>	Decking, Furring, Siding Wooden Fencing, Subfloors Sheathing and Framing

