

INDUSTRIAL CARTON STAPLING SOLUTION

- HIGH SPEED OPERATION
- DURABLE FOR PROFESSIONAL USE
- CURVED ANVILS AVAILABLE FOR VARIOUS APPLICATIONS

Robust **Gravity Casted** frame for extended tool life

Standard Equipped **Air-flow Adjust Port**

Powerful Shuttle Blade for **Pre-Compression** Prior to and During Operation

Special-Treated **Clinch plate** for **Maximum Durability**

6"x1" High Throat provides **Flexibility** during usage



CR/CL/DR/DL/B Type Anvils Available for Select



TOOL SPECIFICATION

Weight:	4.8 lbs (2.2kg)
Height:	9.4" (240mm)
Width:	2.2" (55mm)
Length:	14.6" (370mm)
Pressure:	36 to 55 PSI (2.5-3.9 bars)
Air Consumption:	0.4 L/sec @85 psi
Firing Mode:	Trigger fire
Applications:	Corrugated Containers Pallet Boxes, Container Inserts
Capacity	110~250

MODEL NUMBER	STAPLE TYPE	CROWN WIDTH	WIRE THICKNESS	WIRE WIDTH	STAPLE LENGTH
PS50-10B	SB 103020	1/2" (12.95mm)	0.020" (0.50mm)	0.103" (2.60mm)	3/8~5/8" (10~15mm)
PS50-5B	SB 5019	1/2" (12.85mm)	0.022" (0.55mm)	0.050" (1.27mm)	1/4~5/8" (6~15mm)
PS50-777	JK 777	1/2" (12.3mm)	0.026" (0.65mm)	0.090" (2.25mm)	3/8~5/8" (10~15mm)
PS50-779	JK 779	1/2" (12.3mm)	0.020" (0.50mm)	0.103" (2.60mm)	5/16~5/8" (8~15mm)

