EVERWIN

# SN412S2

**Wide Crown Heavy-Wire Stapler**

***SPEED, POWER, DURABILITY, ALL IN 1***

- **ALL METAL HOUSING AND STRUCTURE**
- **ONE-PIECE ALUMINUM CYLINDER DESIGN**
- **PNEUMATIC POWER ADJUSTMENT KNOB**
- **HIGH SPEED OPERATION, 15~20 CYCLES/SECOND**
- **COMPACT ENGINE BOOSTS MANEUVERABILITY**
- **FULL AUTOMATIC VERSION AVAILABLE (SN412S2A)**

**STEEL HAMMER EXHAUST**

**ALUMINUM ERGONOMIC FRAME**
**OVER-MOLDED HANDLE GRIP**

**ENLARGED REAR RESERVOIR**
Minimizes Staple Stair Stepping

**RUBBER PROTECTION PAD**
Protects Work Surface

**HIDDEN DEPTH ADJUST KNOB**
with
**INVESTMENT -CASTED COVER**

**TOOL-FREE REAR JAM CLEARANCE**
**REAR EXHAUST**
Minimizes Downtime and Maximizes
Tool Durability & Operation Comfort

**INDUSTRY-LEADING LATHING STAPLING SOLUTION**

| FASTENER SPECIFICATION | |
|---|---|
| **Type:** | 16 Ga. "BCS2" Staples |
| **Fastener Lengths:** | 25~50mm (1"~2") |
| **Crown Width** | 25.4mm (1") |
| **Shank Diameter:** | 1.60x1.40mm |
| **Shank Type:** | Smooth |
| **Load Capacity:** | 160 |
| **Applications:** | Wire Lathing, Furniture Framing, Foam Insulation |

| TOOL SPECIFICATION | |
|---|---|
| **Weight:** | 4.6lbs (2.1kg) |
| **Height:** | 8.9" (225mm) |
| **Width:** | 2.5" (64mm) |
| **Length:** | 14.0" (355mm) |
| **Operating Pressure:** | 70 to 120 PSI (5-8 bars) |
| **Firing Mode:** | Contact fire |
| **Air Consumption:** | 1.27cfm (0.6L/sec) @80psi |
| **Noise Level:** | LPA 1sd: 91.80<br>LWA 1sd: 97.60 |
| **Vibration:** | < 2.5 / N/A $m/s^2$ |

Telephone: (886) 4 2333 -2999 Fax: (886) 4 2333 -0555
No. 7, Wugong 7th Road, Wufeng District, Taichung City, 413, Taiwan
E-mail: sales@everwinpneumatic.com Website: www.everwinpneumatic.com