

YOUR FIRST ROOFING OPTION

- ALL METAL HOUSING AND STRUCTURE
- ONE-PIECE ALUMINUM CYLINDER DESIGN
- PNEUMATIC POWER ADJUSTMENT KNOB
- HIGH SPEED OPERATION, 15~20 CYCLES/SECOND
- COMPACT ENGINE BOOSTS MANEUVERABILITY

**DRIVING
POWER
ADJUSTABLE**



FASTENER SPECIFICATION	
Type:	16 Ga. "BCS2" Staples
Fastener Lengths:	19~38mm (3/4"~1-9/16")
Crown Width	25.4mm (1")
Shank Diameter:	1.60x1.40mm
Shank Type:	Smooth
Load Capacity:	160
Applications:	Shingle Roofing, House Wrap/Vapor Barrier, Sheathing

TOOL SPECIFICATION	
Weight:	5.3lbs (2.4kg)
Height:	8.9" (225mm)
Width:	2.5" (64mm)
Length:	14.0" (355mm)
Operating Pressure:	70 to 120 PSI (5-8 bars)
Firing Mode:	Contact fire
Air Consumption:	1.27cfm (0.6L/sec) @80psi
Noise Level:	LPA 1sd: 91.80 LWA 1sd: 97.60
Vibration:	< 2.5 / N/A m/s ²

