

SPEED, POWER, DURABILITY, ALL IN 1

- ALL METAL HOUSING AND STRUCTURE
- ONE-PIECE ALUMINUM CYLINDER DESIGN
- PNEUMATIC POWER ADJUSTMENT KNOB
- HIGH SPEED OPERATION, 15~20 CYCLES/SECOND
- COMPACT ENGINE BOOSTS MANEUVERABILITY
- FULL AUTOMATIC VERSION AVAILABLE (SN41S2A)

STEEL HAMMER EXHAUST

ALUMINUM ERGONOMIC FRAME
OVER-MOLDED HANDLE GRIP

ENLARGED REAR RESERVOIR
Minimizes Staple Stair Stepping

RUBBER PROTECTION PAD
Protects Work Surface



HIDDEN DEPTH ADJUST KNOB
INVESTMENT-CASTED COVER

TOOL-FREE REAR JAM CLEARANCE
REAR EXHAUST

Minimizes Downtime and Maximizes
Tool Durability & Operation Comfort

FASTENER SPECIFICATION

Type:	16 Ga. "BCS2" Staples
Fastener Lengths:	19~40mm (3/4"~1-9/16")
Crown Width	25.4mm (1")
Shank Diameter:	1.60x1.40mm
Shank Type:	Smooth
Load Capacity:	160
Applications:	Furniture Framing, Wire Lathe, Foam Insulation Board

TOOL SPECIFICATION

Weight:	5.1lbs (2.3kg)
Height:	8.9" (225mm)
Width:	2.5" (64mm)
Length:	14.0" (355mm)
Operating Pressure:	70 to 120 PSI (5-8 bars)
Firing Mode:	Contact fire
Air Consumption:	1.27cfm (0.6L/sec) @80psi
Noise Level:	LPA 1sd: 91.80 LWA 1sd: 97.60
Vibration:	< 2.5 / N/A m/s ²

